



## RESIDUAL CURRENT CIRCUIT BREAKER WITH OVERLOAD PROTECTION 3P+N C 20A 30mA 6kA TYPE A PL8M4

Code: 500-43563

### TECHNICAL DATA

|                                                |                          |
|------------------------------------------------|--------------------------|
| Supply Voltage (V):                            | 400V                     |
| Amperage (A):                                  | 20A                      |
| Operating Frequency (Hz):                      | 50/60Hz                  |
| Ingress Protection (IP):                       | IP20                     |
| Operating Temperature °C:                      | -25°C - +65°C            |
| Product Color:                                 | Λευκό/White, Blue handle |
| Product Material:                              | PA66                     |
| Product Net Weight (kg):                       | 0.426                    |
| Product Gross Weight (kg):                     | 0.426                    |
| Packing (pcs):                                 | 3/30                     |
| Packaging:                                     | Box with Sticker         |
| Height:                                        | 75mm                     |
| Width:                                         | 71.6mm                   |
| Length:                                        | 81mm                     |
| Guarantee Eurolamp:                            | 2 Χρόνια/ 2 Years        |
| Certifications:                                | Ναι/Yes                  |
| CE Mark:                                       | Ναι/Yes                  |
| Cable Cross Section:                           | 25mm <sup>2</sup>        |
| Busbar Type:                                   | U Type                   |
| Poles (Gacia):                                 | 4                        |
| Contact Position Indication (Gacia):           | Yes                      |
| Rated Short Circuit Breaking Capacity (Gacia): | 6kA                      |
| Breaking Capacity (Gacia):                     | 6kA                      |
| mA (Gacia):                                    | 30                       |
| Product Standard (Gacia):                      | IEC61009                 |



# EUROLAMP®

Pioneers in New Technology !

|                                           |                                                           |
|-------------------------------------------|-----------------------------------------------------------|
| Service Life (Gacia):                     | Μηχανικό/ Mechanical: 6000,<br>Ηλεκτρικό/Electrical: 3000 |
| Curve (Gacia):                            | C                                                         |
| Terminal Connection Type (Gacia):         | Καλώδιο/Wire                                              |
| Residual Current Protection Type (Gacia): | A                                                         |

