

HRN-100/2



Specificatii

Cod ETI	002470303
Descriere	HRN-100/2
Denumire clasă	Relevu control
Func ie	Relee monitorizare și control
Tensiunea de alimentare (V)	400V
Tipul de control	Umax,Umin,sequence phase,phase and neutral failure,frequency
Numarul de contacte	2
Tipul voltajului	AC
Curent nominal (A)	5A
Capacitatea maxima de incarcare AC1 (VA)	1200VA
Număr contacte CO	1

[Pagina de produse online](#)

Alta documentatie

[Catalog caracteristici tehnice](#)[Model 3D](#)[2D mușchi](#)[Manual de instructiuni](#)[Declaratie CE](#)[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC001438
Denumire clasă	Voltage monitoring relay
Type of electric connection	Screw connection
Single-phase under voltage possible	1
Three-phase under voltage possible	1
Single-phase over voltage possible	1
Three-phase over voltage possible	1
Single-phase hysteresis possible	1
Three-phase hysteresis possible	1
Contains function DC-under voltage	
Contains function DC-over voltage	
Contains function DC-voltage hysteresis	
Voltage measuring range 1	85...310V
Voltage measuring range 2	150...535V
Type of voltage measuring range	AC
Voltage type for actuating	AC
Response value voltage	90...500V
Min. adjustable delay-on energization time	0,1s
Max. permitted delay-on energization time	999s
Min. adjustable off-delay time	0,1s
Max. permitted off-delay time	999s
Number of contacts as change-over contact	2
Width	36mm
Height	90mm
Depth	66,5mm