

ECM12PT



Specificatii

Cod ETI	001101011
Descriere	ECM12PT
Denumire clasă	Cutie distribu ie
Tip montaj	Culoare aplicată
Curent nominal (A)	63A
Clasa de protec ie	II
Grad de protec ie IP	IP40
Numarul de module (total / pe rand)	12
Dimensiune (numarul de randuri)	1
Usa (material, culoare)	Plastic, transparent
Parte inferioara cutie (material, culoare)	Plastic, alb
Numarul de terminale PE/N (conexiuni)	10
Test pentru fire (°C)	650°C

Pagina de produse online 

Alta documentatie



Catalog caracteristici tehnice

Model 3D

2D mușchi

Manual de instructiuni

Declaratie CE

Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000214
Denumire clasă	Small distribution board
Mounting method	Flush-mounted (plaster)
Number of rows	1
Width in number of modular spacings	12
Housing material	Plastic
Height	232mm
Width	283mm
Depth	106mm
Built-in depth	68mm
DIN-rail	1
EMC-version	1
Colour	White
Degree of protection (IP)	IP40

Desen cotat

Flush mounted distribution board

type	Dimensions							Max. allowed power losses when Max. number of devices are installed	Static load
	A	B	C	D	E	F	G	Pde	
ECM4PT/ECM4PO	232 mm	139 mm	99 mm	-	123 mm	216 mm	69 mm	>10 W	520 g
ECM8PT/ECM8PO	232 mm	211 mm	99 mm	-	201 mm	212 mm	68 mm	>16 W	1040 g
ECM12PT/ECM12PO	232 mm	283 mm	106 mm	-	273 mm	212 mm	68 mm	>25 W	1560 g
ECM18PT/ECM18PO	232 mm	392 mm	106 mm	-	382 mm	212 mm	68 mm	>25 W	2340 g
ECM24PT/ECM24PO	357 mm	283 mm	106 mm	125 mm	273 mm	336 mm	68 mm	>30 W	1560 g
ECM36PT/ECM36PO	482 mm	283 mm	106 mm	125 mm	273 mm	462 mm	68 mm	>30 W	1560 g
ECM48PT/ECM48PO	676 mm	283 mm	106 mm	125 mm	273 mm	656 mm	68 mm	>30 W	1560 g
ECM2x18PT/ECM2x18PO	357 mm	392 mm	106 mm	125 mm	382 mm	336 mm	68 mm	>30 W	2340 g
ECM3x18PT/ECM3x18PO	522 mm	392 mm	106 mm	125 mm	382 mm	502 mm	68 mm	>35 W	2340 g

