

ECT36MEDIAPO



Specificatii

Cod ETI	001100213
Descriere	ECT36MEDIAPO
Denumire clasă	Cutie distribu ie
Tip montaj	Suprafa ă montată
Clasa de protec ie	II
Dimensiune (numarul de randuri)	3
Usa (material, culoare)	Plastic, white
Parte inferioara cutie (material, culoare)	Plastic, alb
Test pentru fire (°C)	650°C
Grad de protec ie IP	IP40
Curent nominal (A)	63A
Numarul de module (total / pe rand)	12

Pagina de produse online 

Alta documentatie



Catalog caracteristici tehnice

Model 3D

2D mușchi

Manual de instructiuni

Declaratie CE

Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000214
Denumire clasă	Small distribution board
Mounting method	Surface mounted (plaster)
Number of rows	3
Width in number of modular spacings	12
Type of covering	Door
Cover model	Closed
Housing material	Plastic
Colour	White
Degree of protection (IP)	IP40
Type of closure	Other

Desen cotat

Surface mounted distribution board

type	Dimensions**					Pde*	Static load
	A	B	C	D	E		
ECT4PT/ECT4PO	235 mm	143 mm	98 mm	127 mm	46 mm	>10 W	520 g
ECT8PT/ECT8PO	236 mm	215 mm	102mm	107 mm	120 mm	>16 W	1040 g
ECT12PT/ECT12PO	236 mm	287 mm	112 mm	107 mm	180 mm	>25 W	1560 g
ECT18PT/ECT18PT	236 mm	396 mm	112 mm	107 mm	289 mm	>25 W	2340 g
ECT24PT/ECT24PO	361 mm	287 mm	112 mm	232 mm	180 mm	>30 W	1560 g
ECT36PT/ECT36PO	485 mm	287 mm	112 mm	357 mm	180 mm	>30 W	1560 g
ECT48PT/ECT48PO	652 mm	287 mm	112 mm	482 mm	180 mm	>35 W	1560 g
ECT2x18PT/ECT2x18PO	361 mm	396mm	112 mm	232 mm	289 mm	>30 W	2340 g
ECT3x18PT/ECT3x18PO	526 mm	396mm	112 mm	357 mm	289 mm	>35 W	2340 g
ECT4x18PT/ECT4x18PO	651 mm	396mm	112 mm	357 mm	289 mm	>40 W	2340 g

* Max. allowed power losses when Max. number of devices are installed

**Sizes are also valid for IT distribution boards DIDO-E MEDIA: ECT...MEDIA

