ETIMAT 1N 1p+N B16 6kA



Specificatii

Cod ETI	002191104
Descriere	ETIMAT 1N 1p+N B16 6kA
Denumire clasă	Disjunctor miniatural
Curent nominal (A)	16A
Caracteristică de întrerupere	B
Număr de poli	1+N
Capacitatea de rupere (kA)	6kA
Tipul voltajului	AC
Tensiunea nominala de rezistenta Uimp (kV)	4kV
Tensiune nominală AC (V)	230V
Tensiune nominală DC (V)	230V
Frecven ă nominală (Hz)	50Hz/60Hz
Sec iune transversală nominală	1mm²-10mm²
Standarde	IEC/EN 60898-1
Func ie	MCB

Pagina de produse online

Alta documentatie

Catalog caracteristici tehnice
Certificate
Model 3D
2D mușchi
Manual de instructiuni
Declaratie CE
Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	B
Number of poles (total)	2
Number of protected poles	1
Rated current	16A
Rated voltage	230V
Rated impulse withstand voltage Uimp	4kV
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	6kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	6kA
Voltage type	AC
Frequency	50...50Hz
Current limiting class	3
Concurrently switching neutral conductor	1
Width in number of modular spacings	1
Built-in depth	68mm
Degree of protection (IP)	IP20
Connectable conductor cross section multi-wired	1...10mm²
Connectable conductor cross section solid-core	1...10mm²

Desen cotat

