R 63-22 230V



Specificatii

Cod ETI	002463470
Descriere	R 63-22 230V
Denumire clasă	Contactor modular
Curent nominal Ie AC-1/AC-7 (A)	63A
Tensiunea nominala (V AC)	440V
Tensiunea de control Uc (V AC)	230V
Tip	AC
Frecven ă nominală (Hz)	50Hz/60Hz
Număr contacte NO	2
Număr de contacte NC	2
Func ie	Contactor modular
Grup Catalog	Tip R

Pagina de produse online

Alta documentatie

Model 3D
2D mușchi
Declaratie CE
Eplan mușchi

ETIM clasificare internationala

Clasificare	EC001653
Denumire clasă	Installation contactor for distribution board
Rated operating voltage	230...400V
Rated operation current	63A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	2
Max. incandescent lamp load	8000W
Max. load fluorescent lamp	5100VA
Max. load fluorescent lamp (Duo circuit)	8120VA
Max. load fluorescent lamp (parallel compensated)	3740VA
Slider for hand switch	
Number of modular spacings	3
Built-in depth	60mm
Additional equipment possible	1
Degree of protection (IP)	IP20

Desen cotat

