

## ETITEC M T2 PV 1100/20 Y



### Specificatii

Cod ETI	002440515
Descriere	ETITEC M T2 PV 1100/20 Y
Denumire clasă	Protec ie supratensiuni
Numarul de module	3
Parte superioara - Nivel de protectie a tensiunii (kV)	3.8kV
Tip curent	DC
Instalare	Protec ie PV
Func ie	SPD
Utilizare (IEC/VDE)	II / C
Număr de poli	2
Grad de protec ie IP	IP20
Tip	T2
Semnalare la distan ă	NU
DC max continuous operating voltage U <sub>c</sub>	1100V
Adancime incorporata (mm)	70mm
Tehnologie aplicata	MOV
Curent de scurgere	DA
In (8/20)	20kA
Grup Catalog	ETITEC M PV

Pagina de produse online [🔗](#)

### Alta documentatie



Catalog caracteristici tehnice

Model 3D

2D mușchi

Manual de instructiuni

Declaratie CE

Eplan mușchi

## ETIM clasificare internationala

Clasificare	EC000941
Denumire clasă	Surge protection device for power supply systems
System configuration DC	1
System configuration IT	
System configuration TN	
System configuration TN-C	
System configuration TN-C-S	
System configuration TN-S	
System configuration TT	
System configuration other	
Number of conductors (without earthing)	2
Nominal discharge surge current (8/20)	20
Short-circuit breaking capacity (I <sub>sc</sub> )	11
Max. discharge surge current (8/20)	40
Max. continuous voltage DC	1100
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	3 modular spacing
Max. PV-voltage	916
Voltage protection level	3,8
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
With remote signalling contact	
Integrated backup fuse	
Signalling at the device	Optical
Category type 2	1
Degree of protection (IP)	IP20